



Bernite 35

Bernite 35 is a powdered compound designed for cleaning heavy deposits of shellac on tablet coating equipment and other surfaces in pharmaceutical and food plants. More recently Bernite 35 has been found to be extremely effective on residues resulting from acrylic polymer aqueous dispersions. (Eudragit coatings)

Bernite 35 cleans well even in cold water and rinses easily and completely with excellent wetting-out action and superior sudsing ability. In addition, Bernite 35 has excellent sequestering action which minimizes hard water problems. It is ideal for in place cleaning, high pressure spray equipment, tank immersion or manual cleaning by brush.

This economical-to-use cleaner finds wide application in pharmaceutical and food processing plants and has proven acceptable to the U.S. Departmental of Agriculture “in all departments of official establishments operating under the Federal meat, poultry, shell egg grading and egg products inspection program.”

Use 2 to 8 ounces per gallon of water at 130°F to 175°F for most applications. The higher concentrations and temperatures can be used for heavier and more resistant deposits. Bernite 35 has been colored with a food grade greenish granular particle to prevent incorrect use or application of this product.

When preparing new solutions or adding to existing ones, slowly add Bernite 35 while stirring to avoid spattering. Do not add large amounts of powder at any one time and do not add to a solution warmer than 100°F.

Features & Benefits

Effective cleaning on shellac and acrylic polymer dispersions	Cleans well in cold water
Excellent sequestering action to minimize hard water problems	Ideal for high pressure spray, immersion, or brush cleaning

Surface Tension Evaluation

Compare water surface tension (35 dynes/square centimeter) to rinse water. A reduction of surface tension in rinse water indicates continued presence of surfactant.



Waste Disposal

To dispose, neutralize with suitable acidic material, dilute and discharge in accordance with federal, state, and local regulations.

Caution

Bernite 35 is a highly alkaline material. Direct contact causes burns. Immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes get medical attention. Harmful if swallowed - get immediate medical attention. Wear rubber gloves, safety goggles or face shield and suitable protective clothing. Use with adequate ventilation.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.